

imageRUNNER ADVANCE DX C7700 Series

SECURE A3 COLOUR MULTIFUNCTION DEVICES TO SUPPORT YOUR BUSINESS' DIGITAL TRANSFORMATION WITH ADVANCED CLOUD SOLUTIONS


MAIN CONFIGURATION OPTIONS



Canon uniFLOW Online
Outstanding Best Office Management Solution




New to the Line




STAPLE FINISHER-AC1

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65 sheets (90 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple on Demand 65 sheets (90 gsm)
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)




BOOKLET FINISHER-AC1

- 3 tray, 3,500 sheet capacity
- Corner and double stapling up to 65
- Supports optional internal 2/4 and 4 hole inner punchers (2/4 Hole Puncher Unit-A1 and 4 Hole puncher unit-A1)




DOCUMENT INSERTION UNIT-Q1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100 sheet capacity




DOCUMENT INSERTION/FOLDING UNIT-K1

- Insert pre-printed sheets
- Up to A3
- 1-tray, 100-sheet capacity
- Z-fold and C-fold




IR ADV DX C7765I / C7770I / C7780I



PAPER DECK UNIT-E1

- Supports A4
- Media weight 52 – 256 gsm
- 3,500 sheets (80gsm)




POD DECK LITE-C1

- Supports up to A3
- Media weight 52 – 300 gsm
- 3,500 sheets (80 gsm)



UNIFLOW ONLINE

- Device-based Cloud Subscription for Document Output and Capture Management



IMAGEPASS-N2

PDL • PCL/PS

MEMORY • 4GB/500GB

SYSTEM • Fiery FS350

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Personalised printing with the built-in, entry-level Fiery FreeForm (TM) or with the supported industry-leading variable data printing (VDP) formats
- Integrates print production workflows with EFI (TM) management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules

This flat configuration is for illustration purpose only. For a complete list of options and the exact compatibility relationships, please refer to the online [product configurator](#).

The Unified Firmware Platform (UFP) ensures that the latest feature upgrades and protection are available, for an enhanced user experience across the entire IR ADVANCE DX portfolio.

imageRUNNER ADVANCE DX C770i

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

MAIN UNIT			
Machine type	A3 Color Laser Multifunctional	Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT, J/K/S/T** (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts*
Core functions	Print, Copy, Scan, Send, Store and Optional Fax	Print Features	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced hold printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer
Processor	1.7GHz Dual Core Processor	Operating System	UFRII: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later) PCL: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019 PS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X(10.10 or later) PPD: Windows®7/8.1/10, Mac OS X(10.9 or later) As of July,2019.
Control Panel	Standard: 10.1" TFT LCD WSVGA Color Touch panel Optional: 10.4" TFT LCD SVGA Color Upright Touch Panel	Copy SPECIFICATIONS	
Memory	Standard: 4.0GB RAM	Copy Speed (BW/CL)	IR-ADV DX C7780i: Up to 80/70 ppm (A4, A5*, A5R, A6R*), Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R) IR-ADV DX C7770i: Up to 70/65 ppm (A4, A5*, A5R, A6R*), Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R) IR-ADV DX C7765i: Up to 65/60 ppm (A4, A5*, A5R, A6R*), Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R) *A5/A6R (1-sided)
Hard Disk drive	Standard*: 320 GB(available disk space: 250 GB), Optional: 250GB, 1TB * A different initial HDD may be used.	First-Copy-Out Time (A4) (BW/CL)	IR-ADV DX C7780i: Approx. 4.4/5.4 seconds or less IR-ADV DX C7770i: Approx. 4.8/5.9 seconds or less IR-ADV DX C7765i: Approx. 4.8/5.9 seconds or less
Mirroring Hard Disk Drive	Optional	Copy resolution (dpi)	600 x 600
Interface Connection	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN(IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy OTHERS Standard: USB 2.0(Host) x1, USB 3.0(Host) x1, USB 2.0(Device) x1 Optional: Serial Interface, Copy Control Interface	Multiple Copies	Up to 9,999 copies
Paper Supply Capacity (A4, 80gsm)	Standard: 3,550 sheets 250-sheet Multi-purpose tray, 1,100-sheet Paper Deck x 2, 550-sheet Paper Cassette x 2 Maximum: 7,050 sheets (with Paper Deck Unit-E1 or POD Deck Lite-C1)	Copy Density	Automatic or Manual (9 Levels)
Paper output capacity (A4, 80gsm)	250 sheets (with Copy Tray-R2) Maximum: 3,500 Sheets (with Staple Finisher-AC1 or Booklet Finisher-AC1)	Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%(1:1), 141%, 200%, 400%
Finishing capabilities	With options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand, Document Insertion, Z-fold, Half-fold, C-fold	Copy Features	Preset R/E Ratios by Area, Two-Sided, Density Adjustment, Original Type Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Merge Job Blocks, Mirror Image, Store in Mail Box, Superimpose Image, Copy ID Card, Skip Blank Pages, Free Size Original, Color Mode, Reserved copy, Copy Sample
Supported media types	Multi-purpose tray: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope Paper Decks(Right/Left): Thin, Plain, Recycled, Color, Heavy, Tracing, Bond, Transparency, Bond, Pre-punched, Letterhead Paper Cassettes (Upper/Lower): Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Tab*, Envelope** * Tab Feeding Attachment-F1 is required ** Envelope Feeder Attachment-F1 is required.	SCAN SPECIFICATIONS	
Supported media sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Free size: 100.0 x 148.0 mm to 330.2 x 487.7 mm Envelope custom size: 98.0 x 148.0 mm to 330.2 x 487.7 mm Paper Decks (Right/Left): Standard size: A4, B5 Paper Cassettes(Upper/Lower): Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 139.7 x 182.0 mm to 330.2 x 487.7 mm Envelope: COM10 No.10, Monarch, DL, ISO-C5 Envelope custom size: 98.0 x 148.0 mm to 330.2 x 487.7 mm	Type	Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)] *Detect Feeder Multi Sheet Feed is supported.
Supported media weights	Multi-purpose tray: 52 to 300 gsm Paper Deck (Right/Left): 52 to 220 gsm Paper Cassette (Upper/Lower): 52 to 256 gsm Duplex: 52 to 220 gsm	Document Feeder Paper Capacity (80 gsm)	Up to 200 Sheets
Warm-up Time	Quick startup mode: 4 seconds or less** **Time from device power on to when the copy icon appears and is enabled to operate on the touch panel display From Sleep Mode: 30 Seconds or Less From Power On: 30 seconds or less** **Time from device power-on, until copy ready(not print reservation)	Acceptable originals and weights	Platen: Sheet, Book, and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 220 gsm (BW, CL) 2-sided scanning: 38 to 220 gsm (BW, CL) *An acceptable weights of A6R or smaller is 50 to 220gsm.
Dimensions (W x D x H)	689 x 937 x 1,185 mm	Supported media sizes	Platen: max. scanning size up to 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R, Custom size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
Installation Space(W x D)	Basic: 2,026 x 1,524 mm (with Front door open + Multi-purpose tray/upper-right cover open + Buffer Pass-M1 + Booklet Finisher-AC1/extension tray & rotary tray extended) Fully Configured: 2,621 x 1,524 mm (with POD Deck Lite-C1 + Buffer Pass-M1 + Document Insertion Unit-G1 + Booklet Finisher-AC1/extension tray extended)	Scan Speed (ipm: BW/CL; A4)	1-sided Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, copy), 2-sided Scanning: 270/270 (300 x 300 dpi, send), 160/90 (600 x 600 dpi, copy)
Weight	Approx. 255 kg (including toner)	Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send (Push): 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
PRINT SPECIFICATIONS		Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA Supported OS: Windows®7/8.1/10/Server2008/Server2008 R2/Server2012/Server2012 R2/Server 2016
Print Speed (BW/CL)	IR-ADV DX C7780i: Up to 80/70 ppm (A4, A5*, A5R, A6R*), Up to 40/35 ppm (A3), Up to 56/49 ppm (A4R) IR-ADV DX C7770i: Up to 70/65 ppm (A4, A5*, A5R, A6R*), Up to 35/32 ppm (A3), Up to 49/46 ppm (A4R) IR-ADV DX C7765i: Up to 65/60 ppm (A4, A5*, A5R, A6R*), Up to 32/30 ppm (A3), Up to 46/42 ppm (A4R) *A5/A6R (1-sided)	Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Space, Scan to Network, Scan to USB Memory Key, Scan to Mobile device, Scan to cloud (uniFLOW Online)
Print Resolution (dpi)	2,400 x 2,400	SEND SPECIFICATIONS	
Page description languages	Standard: UFR II, PCL6, Adobe® PostScript®3™	Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
Direct Print	Supported file types: PDF, EPS, TIFF, JPEG, and XPS	Address Book	LDAP (2,000)/Local(1,600)/Speed dial(200)
Printing from mobile and cloud	AirPrint, Mopria, Google Cloud Print, Canon Business PRINT, and uniFLOW Online A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.	Send resolution (dpi)	Push: up to 600 x 600 Pull: up to 600 x 600
		Communication protocol	File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV E-mail/Fax: SMTP, POP3
		File Format	Standard: TIFF, JPEG, PDF(Limited Color, Compact, Searchable, Apply policy, Optimize for Web, PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS(Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)

imageRUNNER ADVANCE DX C7770i

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Pages

FAX SPECIFICATIONS

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 kbps
G3: 14.4 kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)

Sending/Receiving Size

Sending: A3, A4, A4R, A5¹, A5R¹, B4, B5², B5R¹
Receiving: A3, A4, A4R, A5R, B4, B5, B5R

¹ Sent as A4

² Sent as B4 short

FAX memory

Up to 30,000 pages (2,000 jobs)

Speed dials

Max. 200

Group dials/destinations

Max. 199 dials

Sequential broadcast

Max. 256 addresses

Memory backup

Yes

Fax Features

Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log

STORE SPECIFICATIONS

Mail Box (Number supported)

100 User Inboxes,
1 Memory RX Inbox,
50 Confidential Fax Inboxes
Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Space

Communication Protocol: SMB or WebDAV
Supported Client PC: Windows[®] 8.1/10
Concurrent Connections (Max.): SMB:64, WebDAV:3

Advanced Space available disc space

Standard:16 GB
(With option: max. 480GB.)

Advanced Space Features

Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support, Search, File Preview, Authentication Management, Open to public, URI TX, Backup/Restore

SECURITY SPECIFICATIONS

Authentication and Access Control

User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

Document Security

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print[™]), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle[®] Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Space Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)
[™] Requires uniFLOW Online / uniFLOW

Network Security

TLS 1.3, IPsec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), Communication Line Separation (G3 FAX, USB Port, Advanced Space, Scan and Send -Virus Concerns for E-mail Reception)

Device Security

Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data Overwrite Erase, HDD Lock), Standard HDD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection), Comply IEEE2600.2 (Common Criteria Certification) (TBD) Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

ENVIRONMENTAL SPECIFICATIONS

Operating Environment

Temperature: 10 to 30 °C
Humidity: 20 to 80 % RH (Relative Humidity)

Power source

iR-ADV DX C7780i: 220-240V 50/60Hz 11A
iR-ADV DX C7770i/C7765i: 220-240V 50/60Hz 10A

Power consumption

Maximum: Approx. iR-ADV DX C7780i: 2,500 W,
iR-ADV DX C7770i/C7765i: 2,000 W
Copying (with DADF continuous scan): Approx. 1.319 W¹
Standby: Approx. 119.6 W¹
Sleep mode: Approx. 0.9 W²
¹ Reference value: measured one unit
² 0.9W sleep mode is not available in all circumstances due to certain settings.

Typical Electricity Consumption (TEC) :

iR-ADV DX C7780i: (BW): 1.35 kWh

iR-ADV DX C7770i: (BW): 119 kWh

iR-ADV DX C7765i: (BW): 114 kWh

Note:

Regarding ENERGY STAR program, the EU-US agreement expired on 20 February 2018. Although TEC values are provided, ENERGY STAR certification is not valid in Europe.

ENERGY STAR Product Specification for Imaging Equipment Version 3.0

Sound Power Level (LWA_m)

Active(BW) (1-sided)

iR-ADV DX C7780i/C7770i/C7765i: 5.1 B*, Kv 0.3 B*

*Reference value: measured only one unit with ISO7779, described with ISO9296:(2017)

Sound Pressure (Lp_Am)

Bystander's position:

Active (BW/CL) (1-sided)

iR-ADV DX C7780i: 57 dB*/56 dB*

iR-ADV DX C7770i: 56 dB*/56 dB*

iR-ADV DX C7765i: 56 dB*/55 dB*

Stand-by

iR-ADV DX C7780i/C7770i/C7765i: 36 dB*

*Reference value: measured only one unit with ISO7779, described with ISO9296 (2017)

Blue Angel

Noise levels (BW/CL)

Standards

CONSUMABLES

Toner Cartridges

Toner Yield (Estimated @ 5% Coverage)

C-EXV 52 Toner BK/C/M/Y

C-EXV 52 Toner BK: 82,000 pages

C-EXV 52 Toner C/M/Y: 66,500 pages

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting

Universal Login Manager (ULM)
[uniFLOW Online Express](#)

Remote management tools

iW Management Console
eMaintenance
Content Delivery System

Scanning software

Network ScanGear

Optimisation tools

Canon Driver Configuration Tool
NetSpot Device Installer

Platform

MEAP (Multifunctional Embedded Application Platform)

Document Administration

Kofax Power PDF (Optional)

FIERY PRINT CONTROLLER SPECIFICATIONS (EMBEDDED)

Optional/Standard

Optional

Name

imagePASS-N2 V1.1 (Embedded)

Print Resolution (dpi)

1200 x 1200, 600 x 600

Page Description Language(s)

Adobe PS3, PCL6

Memory

4GB (1 x 4GB)

Hard Disk Drive

500 GB SATA

Processor Speed

Intel Pentium G4400 (3.3 GHz)

System

FS350

Fonts

PS: 138 Fonts

PCL: 113 Fonts

Supported Operating Systems

Windows[®] 7 64 bit/Windows 8.1 64 bit/Windows10 64 bit/
Windows Server 2008 R2 64 bit only/Windows Server 2012
64 bit only (Only Printer driver support!)/ Windows Server
2012 R2 64 bit only/Windows Server 2016 R2 64 bit only/
MAC OS (10.11, 10.12, 10.13, 10.14)

Interface

2 x Ethernet (1000Base-T/100Base-TX/10Base-T), USB3.0 x
2 (Rear), USB2.0 x 4 (Rear)

Network protocols

TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB,
LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing,
Port9100, SNTP, 802.1X, DHCP, DNS, NTP)

Direct Print

PDF1.7, EPS, TIFF6, JDF1.4/JMF(Optional)

VDP

FreeForm v1, v2.1

Fiery Print Controller Standard Features

Fiery Command WorkStation 6/Paper Catalog/Fiery Spot-On/
Fiery Remote Scan/Fiery Hot Folders & Virtual Printers

Fiery Print Controller Options

Fiery Impose/Fiery Compose/Fiery Impose and Compose/
Productivity Package Web Activate (Include Fiery JDF)

HW Platform

E400

Base OS

Debian of Linux

Power source

AC100-240V, 50Hz/60Hz, 3.0A (100V) - 1.3A (240V)

Maximum Power consumption

47 W

Dimensions (W x D x H)

285 x 93 x 295 mm

Weight

Fiery unit only (with plate): 5 kg

imageRUNNER ADVANCE DX C7770i

TECHNICAL SPECIFICATIONS

imageRUNNER ADVANCE DX C7700 Series

PAPER SUPPLY OPTIONS

Paper Deck Unit-E1

Paper Capacity: 3,500 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead
Paper Size: A4, B5
Paper Weight: 52 to 256 gsm
Power Source: from the Main Unit
Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit)
Weight: Approx. 34 kg

POD Deck Lite-C1

Paper Capacity: 3,500 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Tracing, Bond, Transparency, Label, Pre-punched, Letterhead, Tab, Envelope*
Paper Size: SRA3, A3, B4, A4, A4R, A5R, B5, B5R, Envelope (COM10 No10, Monarch, DL, ISO-C5), Custom size: 139.7 x 148.0 mm to 330.2 to 487.7 mm
Paper Weight: 52 to 300 gsm
Power Source: 220-240V/1.2A 50/60Hz
Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit)
Weight: Approx. 68 kg
*Envelope Feeder Attachment-G1 is required.

OUTPUT OPTIONS*

Copy Tray-R2

Provides a simple tray for basic output needs.
Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)
Dimensions (W x D x H): 420 x 382 x 175 mm

Staple Finisher-AC1(External)

Tray Capacity (with 80gsm paper):
Upper Tray: A4, A5, A5R, A6R, B5: 250 sheets
SRA3, A3, A4R, B4, B5R: 125 sheets
Envelope: 30 sheets
Mid Tray: Same as upper tray
Lower Tray: A4, A5, A5R, B5: 3,000 sheets
SRA3, A3, A4R, B4, B5R: 1,500 sheets
A6R: 250 sheets
Envelope: Monarch: 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets
Paper Weight:
Upper Tray: 52 to 256 gsm
Mid Tray: same as Upper tray
Lower Tray: 52 to 300 gsm
Staple Position: Corner, Double
Staple Capacity:
A4/B5: 65 sheets (52 to 90 gsm)
A3/A4R/B4: 40 sheets (52 to 90 gsm)
Eco Staple:
A3/A4: 5 sheets (52 to 64 gsm)
4 sheets (65 to 81.4 gsm)
3 sheets (82 to 105 gsm)
Staple On Demand: 65 sheets (52 to 90 gsm)
Power supply: From the main unit
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
Weight: Approx. 36 kg

Booklet Finisher-AC1 (External)

(Includes the above Staple Finisher-AC1 basic staple specifications.)
Saddle Stitch paper size: A3, A4R, B4, Custom Size (195.0 x 270.0 mm to 304.8 x 457.2 mm)
Saddle Stitch Staple Capacity: up to 20 sheets x 10 sets (52 to 81.4 gsm) (including 1 cover sheet up to 256 gsm)
Non Staple Folded Bunch Capacity: up to 3 sheets (52 to 105 gsm)
Power supply: From the main unit
Dimensions (W x D x H): 656 x 623 x 1,195 mm (when the extension tray and rotary tray are extended)
Weight: Approx. 60 kg

2/4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
Two or Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Two holes A3, A4, A4R, A5, B4, B5, B5R
Four holes A3, A4
Power Source: From the finisher

4 Hole Puncher Unit-A1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
Four Holes
Acceptable Punch Paper Weight: 52 to 300 gsm
Acceptable Punch Paper Size:
Four holes A3, A4, A4R, A5, B4, B5, B5R
Power Source: From the finisher

Document Insertion Unit-G1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
Number of trays: 1
Tray Capacity: Up to 100 Sheets (80 gsm)
Acceptable Paper Type: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Letterhead, Tab
Acceptable Paper Sizes: SRA3, A3, A4, A4R, B4, B5, B5R
Acceptable Paper Weight: 60 to 256 gsm
Power Source: 100-240V/50/60Hz 1.0A
Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray)
Weight: Approx. 40 kg

Document Insertion/Folding Unit-K1

(Requires either the Staple Finisher-AC1 or Booklet Finisher-AC1)
Number of trays: 1
Supported Folding Type: Z-Fold, C-Fold
Acceptable Paper Type: Z-Fold, C-Fold
Insertion Unit: Thin, Plain, Recycled, Color, Heavy, Coated, Textured, Bond, Letterhead, Tab
Z-Fold/C-Fold: Thin, Plain, Recycled, Color
Acceptable Paper Sizes:
Insertion Unit: SRA3, A3, A4, A4R, B4, B5, B5R
Z-Fold: A3, A4R, B4
C-Fold: A4R
Acceptable Paper Weight:
Insertion Unit: 60 to 256 gsm
Z-Fold/C-Fold: 60 to 105 gsm
Tray Capacity (with 80 gsm paper):
Insertion: Up to 100 Sheets
Z-Fold*: A3, B4: 30 sheets
A4R: 10 sheets
C-Fold: A4R: 40 sheets
*Z-Fold output to the Staple Finisher-AC1 or Booklet Finisher-AC1
Power Source: 100-240V/50/60Hz 1.0A
Dimensions (W x D x H): 247 x 679 x 1,242 mm (attached to the device: width excluding document tray)
Weight: Approx. 76 kg

HARDWARE ACCESSORIES

Card Readers

MICARDPLUS FOR ULM
Copy Card Reader-F1
Copy Card Reader Attachment-A4

Others

Utility Tray-B1
Printer Cover-H2
Tab Feeding Attachment-F1
Upright Control Panel-J1
Numeric Keypad-A1
Finisher Jogger Kit-A1
Envelope Feeder Attachment-F1
Envelope Feeder Attachment-G1

SECURITY OPTIONS

Data Security

HDD Mirroring Kit-J1
2.5inch/250GB HDD-N1
2.5inch/1TB HDD-P1

SYSTEM AND CONTROLLER OPTIONS

Print Accessories

PCL International Font Set-A1

Barcode Printing

Barcode Printing Kit-D1

EFI-Fiery Based Controller

imagePASS-N2 V1.1

EFI-Fiery Based Controller Options

Fiery Impose
Fiery Compose
Fiery Impose and Compose

System Accessories

Copy Control Interface Kit-A1
Connection Kit-A2 for Bluetooth LE
Serial Interface Kit-K3
NFC Kit-E1

Fax Accessories

Super G3 FAX Board-AS1
Super G3 2nd Line Fax Board-AS1
Remote Fax Kit-A1
IP FAX Expansion Kit-B1

OTHER OPTIONS

Accessibility Accessories

ADF Access Handle-A1
Voice Guidance Kit-G1
Voice Operation Kit-D1

Staple Cartridge

Staple-N1
Staple-P
Staple Cartridge-X1
Staple Cartridge-Y1

Software & Solutions



Certifications and compatibility



Canon Ireland
3006 Lake Drive
Citywest, Saggart
Co. Dublin, Ireland
Telephone No: 01 2052400
Facsimile No: 01 2052525
canon.ie

Canon (UK) Ltd
5 The Square
Stockley Park
Uxbridge
UB11 1ET
Tel: 01895 648 000
www.canon.co.uk

Canon Inc.
canon.com
Canon Europe
canon-europe.com
English edition
© Canon Europa N.V., 2020