



> PRINT > COPY > SCAN > FAX

**TASKalfa 9002i**

A3 BLACK AND WHITE  
MULTIFUNCTIONAL

# HIGH PRODUCTIVITY MATCHED WITH HIGH PERFORMANCE



\*Equivalent 4800 x 1200dpi

Up to 90 pages per minute black and white.

1200x1200 dpi print resolution (2 bit depth\*).

Individual paper handling options, including booklet and tri-folding.

Standard network and optional NFC mobile printing, as well as document scanning.



The TASKalfa 9002i sets new levels of high speed printing for light production environments. With high speed comes high productivity. With a maximum paper input capacity of 7,650 sheets and maximum output capacity of 4,300 sheets this device deals with large print jobs effortlessly and efficiently. A fast processor and large memory ensures print jobs are processed at high speed whilst the optional finisher can deliver completed booklets and tri-folded leaflets in-house. The 9" full colour touch screen also allows operators to quickly and intuitively access the myriad of time saving functions available from this device.



The TASKalfa 9002i incorporates extremely durable components that guarantee efficient and reliable operation, to meet the demanding requirements of busy office environments. The TASKalfa 9002i provides effective productivity and maximum flexibility whilst ensuring minimum impact on the environment.

#### GENERAL

**Technology:** KYOCERA Laser Monochrome, HyPAS™ solution platform  
**Engine speed (pages per minute):** Up to 90/45 ppm A4/A3  
**Resolution:** 1,200 x 1,200 dpi, 2-bit depth for print quality of 4,800 dpi equivalent x 1,200 dpi  
**Warm-up time from power on:** Approx. 30 seconds or less  
**Time to first page:** Approx. 3.6 seconds or less  
**CPU:** Freescale QorIQ T1024 Dual Core 1.4GHz  
**Memory:** 4.5 GB RAM + 8 GB SSD + 320 GB HDD  
**Standard interfaces:** USB 2.0 (Hi-Speed USB), USB Host x 4, Fast Ethernet 10BaseT/100BaseTX/1000BaseT, slot for optional print server, slot for optional SD, SDHC card, slot for optional fax system  
**Dimensions (W x D x H) – main unit**  
 750 x 822 x 1234mm (DP, operation panel included)  
**Weight:** Main unit approx. 150 kg  
**Power source:** AC 220 V – 240 V, 50/60 Hz  
**Power consumption**  
 Printing: 1,340 W  
 Ready mode: 100 W  
 Sleep mode: 1 W or less  
**Noise (sound pressure level ISO 7779/ISO 9296)**  
 Printing: 75 dB(A) LpA  
 Ready mode: 58 dB(A) LpA  
**Safety standards:** GS, TÜV, CE; This unit is manufactured according to ISO 9001 quality standard and ISO 14001 environmental standard. RoHS compatibility

#### PAPER HANDLING

All paper capacities quoted are based on paper thickness of max. 0.11 mm. Please use paper recommended by KYOCERA under normal environmental conditions.  
**Input capacity:** 150-sheet multi-purpose tray, 60 – 300 g/m<sup>2</sup> (banner 136 – 165 g/m<sup>2</sup>), A6R – 305 x 457 mm, banner max. 305 x 1,220 mm; 2x 1,500-sheet high-capacity paper deck, 60 – 256 g/m<sup>2</sup>, A4, B5; 2x 500-sheet universal paper cassette, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm incl. custom paper sizes; Max. input capacity with options: 7,650 sheets A4  
**Document processor:** (one-path duplex scanning) 270 sheets; 35 – 220 g/m<sup>2</sup> (simplex), 50 – 220 g/m<sup>2</sup> (duplex); A6R – Banner up to 2,200 mm  
**Duplex unit:** Duplex as standard supports A5R – 305 x 457 mm, 60 – 256 g/m<sup>2</sup>  
**Output capacity**  
 Standard job separator tray 70 sheets, optional copy tray (D): upper 100 sheets, lower 250 sheets; max. optional output capacity 4,300 sheets

#### PRINT FUNCTIONS

**Controller language:** PRESCRIBE  
**Emulations:** PCL6 (PCL5c / PCL-XL), KPDL3 (PostScript 3 compatible), PDF Direct Print, XPS Direct Print and OpenXPS

**Operating systems:** All current Windows operating systems, Mac OS X Version 10.8 or higher, UNIX, LINUX, as well as other operating systems on request.  
**Fonts/barcodes:** 93 outline fonts (PCL), 136 fonts (KPDL3), 8 fonts (Windows Vista), 1 Bitmap font, 45 types of one-dimensional barcodes plus two-dimensional barcode (PDF-417)  
**Print features:** Encrypted PDF Direct Print, IPP printing, e-mail printing, WSD print, secure printing via SSL, IPsec, SNMPv3, quick copy, proof and hold, Private Print, job storage and job management functionality  
**Mobile printing support:** KYOCERA Mobile Print app for iOS and Android, AirPrint, Mopria, NFC, Direct Wi-Fi, Google Cloud Print

#### COPY FUNCTIONS

**Max. original size:** A3  
**Continuous copying:** 1 – 9999  
**Zoom range:** 25 – 400% in 1% steps  
**Preset magnification ratios:** 5R/5E  
**Digital features:** Scan once copy many, electronic sort, 2-in-1 and 4-in-1 function, image repeat copy, page numbering, cover mode, booklet copy, interrupt copy, form overlay, stamp function and skip-blank-page function.  
**Exposure mode:** Auto, manual: 16 steps  
 Image adjustments: Text + photo, text, photo, map

#### SCAN FUNCTIONS

**Functionality:** Scan-to-email, Scan-to-FTP, Scan-to-SMB, Scan-to-USB Host, Scan-to-box, Network TWAIN, WSD scan  
**Scan speed:** (A4, 300 dpi, Dual Scan) 220 images per minute  
**Scan resolution:** 600 x 600 dpi, 400 x 400 dpi, 300 x 300 dpi, 200 x 400 dpi, 200 x 200 dpi, 200 x 100 dpi (24 bit)  
**Max. scan size:** A3, Banner up to 2,200 mm  
**Original recognition:** Text, photo, text + photo, optimised for OCR  
**File types:** PDF (high compression, encrypted, PDF/A), Searchable PDF (OCR), JPEG, TIFF, XPS, OpenXPS

#### FAX FUNCTIONS (OPTIONAL)

**Compatibility:** ITU-T Super G3  
**Modem speed:** Max. 33.6 kbps  
**Transmission speed:** Max. 3 seconds (JBIG)  
**Fax resolution:**  
 Normal: 200 x 100 dpi  
 Fine: 200 x 200 dpi  
 Superfine: 200 x 400 dpi  
 Ultrafine: 400 x 400 dpi  
 600 x 600 dpi  
**Maximum original size:** A3, Banner up to 1,600 mm  
**Compression method:** JBIG, MMR, MR, MH  
**Features:** Opt. Internet-fax, network faxing, rotate transmission, rotate reception, duplex fax reception, memory reception, mailbox, remote diagnostics, dual fax with second fax system 12

#### CONSUMABLES

**TK-6725 Toner-Kit:** Average continuous toner yield 70,000 pages in accordance with 6% coverage A4  
**WT-861 Waste Toner Bottle**  
 600,000 sheets (in accordance with 6% coverage)  
**Staple cartridge:** SH-10 for BF-730, SH-12 for DF-7110

#### OPTIONS

**Fax System 12**  
**Internet Fax Kit (A)**  
**Paper handling**  
**PF-730(B) Paper feeder**  
 2x 500 sheets, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm, folio  
**PF-740(B) Paper feeder**  
 2x 1,500 sheets, 60 – 256 g/m<sup>2</sup>, A4, B5, letter  
**PF-7130 Paper feeder**  
 500 sheets, 60 – 256 g/m<sup>2</sup>, A5R – 305 x 457 mm  
**PF-7120 A4 side deck:** 3,000 sheets, 60 – 256 g/m<sup>2</sup>, A4, B5  
**DF-7110 Document finisher**  
 Main tray: max. 4,000 sheets A4 (3,000 sheets with BF-730 attachment); max. 60 – 300 g/m<sup>2</sup>; max. B5R – 305 x 457 mm  
 Sub-tray: 200 sheets A4; 60 – 300 g/m<sup>2</sup>; A6R – 305 x 457 mm  
 Sub-tray (top): 100 sheets; 60 – 300 g/m<sup>2</sup>; A6R – A4  
 Stapling up to 65 sheets A4 or 30 sheets A3 at 3 positions, B5 – 305 x 457 mm  
**PH-7C/PH-7D Punch unit for DF-7110**  
 2-hole/4-hole/Swedish type, 60 – 300 g/m<sup>2</sup>, A5R – A3  
**MT-730(B) Mailbox sorter for DF-7110**  
 7 bins x 100 sheets A4, 50 sheets A3/B4, 60 – 163 g/m<sup>2</sup>  
**BF-730 Booklet and tri-folding unit for DF-7110**  
 Half folding: 60 – 256 g/m<sup>2</sup>, A3, B4, A4R  
 Booklet: max. 16 sheets (64 pages, 60 – 90 g/m<sup>2</sup>)  
 Non-staple folding: max. 5 sheets (60 – 90 g/m<sup>2</sup>)  
 Tri-folding: 60 – 105 g/m<sup>2</sup>, A4R  
 Multi tri-folding: 5 sheets (60 – 90 g/m<sup>2</sup>), 3 sheets (91 – 105 g/m<sup>2</sup>)  
**Copy tray (D):** upper tray 100 sheets, lower tray 250 sheets  
**Banner Guide (A):** Banner paper feeding guide, up to 10 sheets  
**Security**  
**Data Security Kit (E):** In line with ISO 15408 (Common Criteria) with security level EAL2  
**USB IC Card Reader:** Card Authentication Kit (B)  
**Keyboardholder 10**  
**Numeric keypad:** NK-7100  
**UG-33 AC:** ThinPrint support  
**UG-34 AC:** Emulation (IBM Proprinter/EPSON LQ-850)  
**Optional interface**  
**IB-35:** Direct Wi-Fi Interface  
**IB-50:** Gigabit-Ethernet board  
 10BaseT/100BaseTX/1000BaseT  
**IB-51:** Wireless Lan Interface



KYOCERA Document Solutions (UK) Ltd  
 Eldon Court, 75-77 London Road, Reading RG1 5BS  
 Tel: 0118 931 1500, Fax: 0118 931 1108  
[www.kyoceradocumentsolutions.co.uk](http://www.kyoceradocumentsolutions.co.uk), [info@deu.kyocera.com](mailto:info@deu.kyocera.com)

\* KYOCERA Document Solutions does not warrant that any specifications mentioned will be error-free. Specifications are subject to change without notice. Information is correct at time of going to press. All other brand and product names may be registered trademarks or trademarks of their respective holders and are hereby acknowledged.

\*\* Depending on the country

YOUR KYOCERA BUSINESS PARTNER

